

# 30P COMPRESSOR

SINGLE-STAGE PISTON SERIES 30 CFM



## Compressor Specifications

|                  |                          |
|------------------|--------------------------|
| Output Capacity: | 30 cfm @ 100 psi         |
| Hydraulic Req:   | 11 gpm @ 1850 psi        |
| Cylinders:       | 4-cylinder, single-stage |
| Max Pressure:    | 150 psi                  |
| Weight:          | 235 lbs.                 |

**The 30P is manufactured for reliability and longevity.** A direct-drive, with no belts to break or adjust, it provides a quick 30 CFM @ 100 PSI. Built around a heavy ductile iron balanced crankshaft with heavy-duty journal bushings and micro-honed connecting rods, it provides smooth operation and long life.

*Air tanks and/or a hydraulic reservoirs are available upon request.*

# 30P SINGLE-STAGE PISTON SERIES 30 CFM

## Durability Standard

- Cast Iron Crankcase Casting
- Cast Aluminum Cylinder Head
- High Temperature Precision Pistons
- Stainless Steel Reed Valves
- Heavy Duty Journal Bushings
- Pulsation Manifold
- Heavy Ductile Iron Crankshaft
- Micro-honed Connecting Rods
- Tapered Roller Bearings
- Pressure Lubricated System
- Oil Pressure Gauge

## Ease of Use

- Canister Air Filters for easy replacement
- Oil dipstick for easy visual check
- Bulkhead fittings for quick hook-up
- Simple and inexpensive to maintain

*Directly driven off of hydraulic motor means no broken belts, ever. The Compressor includes a high capacity hydraulic cooler and fan for cooler operation. One piece cylinder and head design mean that there are no head gaskets to fail.*

\*Specifications may change without notification.

Your Contact:

Telephone: 800-392-3015  
E-mail: [sales@americaneagleacc.com](mailto:sales@americaneagleacc.com)  
[www.americaneagleacc.com](http://www.americaneagleacc.com)

Designed & Manufactured in the U.S.A.  
Copyright © 2016 American Eagle Accessories Group

12/18