



	Model	CFM	Max PSI	GPM Required	Hydraulic Pressure	Length	Width	Height	Weight
Single Stage Piston Series Hydraulic Drive	8P	8 @100 PSI	150	7	1800 PSI	23"	14.5"	17"	120 lbs
	13P	13 @100 PSI	150	7	1800 PSI	25"	14.5"	17"	135 lbs
	30P	30 @100 PSI	150	11	1850 PSI	27"	20"	19.5"	225 lbs
	70P	70 @100 PSI	150	18	2650 PSI	32"	22.5"	22"	325 lbs
TWO-STAGE PISTON SERIES HYDRAULIC DRIVE	23P	23	175	8	2300 PSI	28.5"	19.5"	28.5"	270 lbs
	46P BELT DRIVE	46	175	18	2500 PSI	25.5"	26"	31"	470 lbs
	46P	46	175	18	2500 PSI	34.5"	26"	29.5"	470 lbs
	60P*	60	175	16	2300 PSI	41"	26"	34.5"	625 lbs
	110P*	110	175	24	2300 PSI	44.5"	27.5"	31.5"	750 lbs
ROTARY SERIES HYDRAULIC DRIVE	30R	30 @100 PSI	150	12	1750 PSI	24"	20"	21"	175 lbs
	45R	40 @100 PSI	150	12	2800 PSI	29"	22"	23.5"	310 lbs
	65R	65 @100 PSI	150	18	2750 PSI	29"	22"	23.5"	335 lbs
	130R	130 @100 PSI	150	30	2850 PSI	43"	27.5"	27.5"	640 lbs



Air compressor assemblies include direct drive coupling, oil cooler, fan, and hydraulic motor.  
 All Hydraulic Compressors are Priced as Open Center systems. Closed center systems are available upon request.  
 All measurements are rounded to nearest .5".

Designed and manufactured in the USA  
 Information is subject to change without notice